



Technical Data Sheet.

Permasolid® Matting Component MA 110



Permasolid Matting Component MA 110 produces matt top coats for metal and plastic substrates when used in combination with Permasolid HS Clear Coats and Permasolid HS Automotive Top Coat 275.

- Enables different topcoat gloss levels.
- Allows for elasticity adjustment.

For professional use only!

Spies Hecker simply closer.




An Axalta Coating Systems Brand

Permasolid® Matting Component MA 110


Product preparation - application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Surfaces have to be prepared according to the recommendations in the TDS of the selected quality.



Ready to use



Not applicable

VOC compliant

2004/42/IIB(e)(840) 600: The EU limit value for this product (product category: IIB(e)) in ready to use form is maximum 840 g/l of VOC. The VOC content of this product in ready to use form is maximum 600 g/l.

Permasolid® Matting Component MA 110


Product preparation - application



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Surfaces have to be prepared according to the recommendations in the TDS of the selected quality.



Ready to use



Not applicable

VOC compliant


This product mix is not VOC compliant.

Permasolid® Matting Component MA 110


Products

Permasolid® Matting Component MA 110

Product mix



Mixing ratios with special agents are available in the productmix table on Phoenix and in the specific TDS.



Permasolid® Matting Component MA 110 can be overcoated with itself within 24 hours, with scuff sanding



Clean after use with a suitable solventbased guncleaner.

Remarks

- Material has to be at room temperature (18-25°C) before use.
- Degree of flatness is depending on application. A wet coat gives higher gloss than a light coat.

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our Spies Hecker product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our Spies Hecker product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.