

VOTTELER LACKFABRIK
GmbH & Co. KG
Schwieberdinger Strasse 97/102
70825 Korntal-Muenchingen
Germany
Phone:
+49 711 98 04-5
Fax
+49 711 98 04-642
eMail:
d.info@votteler.com

VOTTELER AG
LACKFABRIK
Wiler Strasse. 3
9536 Schwarzenbach SG
Switzerland
Phone:
+41 71 929 52 82
Fax
+41 71 929 52 84
eMail:
ch.info@votteler.com

VOTTELER
LACKTECHNIK GMBH
Malvenstrasse. 7
4600 Wels
Austria
Phone:
+ 43 72 42 7 59-0
Fax
+ 43 72 42 7 59-113
eMail:
at.info@votteler.com



PRODUCT DESCRIPTION

38055-0-0000

PURIDUR® HARDENER PRIMO RAPIDO

Attributes / Characteristics

Hardener for PURIDUR® Coatings.

Area of application

-

Technical data

Density 0.987– 1.007 g/ml at 20 °C

Shelf life when stored

Un-opened 06 months at 20 °C

Application

Material temperature 20 – 23 °C

Cleaning thinner 19995-0-0000, THINNER FOR NC- AND SHE-LACQUERS

General instructions Once opened, ensure that the container lids are re-closed tightly.
After repeated openings, check suitability of the material for the intended purpose.

Note: PUR- leaflet of the Professional Guild ZH 1/181.

Disposal

In case of disposal, use only waste code numbers recommended by your local authority.

Unit of sales

2.000 Kg. in 3 Liter Flat cans plus GDEC-0025

Safety

Observe instructions on the material safety data sheet and the container label.

Other instructions

For commercial and industrial use only.

Date of last update

11.04.2016

The suitability of the material shall be inspected by the manufacturer with respect to his/her requirements regarding quality, color, and the like, e.g. by a sample staining and/or sample varnishing. The above information is based on our testing and experience. Furthermore, the information does not represent any warranty of any characteristics and thus does also not represent the contractually agreed nature of the product. Additionally, the information does not claim any completeness and it is given without any warranties.