

VOTTELER LACKFABRIK
GmbH & Co. KG
Schwieberdinger Strasse 97/102
70825 Korntal-Muenchingen
Germany
Phone:
+49 711 98 04-5
Fax
+49 711 98 04-642
eMail:
d.info@votteler.com

VOTTELER AG
LACKFABRIK
Wiler Strasse. 3
9536 Schwarzenbach SG
Switzerland
Phone:
+41 71 929 52 82
Fax
+41 71 929 52 84
eMail:
ch.info@votteler.com

VOTTELER
LACKTECHNIK GMBH
Malvenstrasse. 7
4600 Wels
Austria
Phone:
+ 43 72 42 7 59-0
Fax
+ 43 72 42 7 59-113
eMail:
at.info@votteler.com



PRODUCT DESCRIPTION

39996-0-0000 **PURIDUR® THINNER**

Attributes / Characteristics

All purpose Thinner with medium evaporation rate. Suitable for all PURIDUR® lacquers.

Area of application

VARIOPUR®-lacquers

Technical data

Density	0.890 – 0.910 g/ml at 20 °C
Shelf life when stored in	
Original containers	12 months at 20 °C
Recommended	
Recommended	
storage temperature	-10 to +30 °C

Application

Optimum room temperature	20 to 23 °C
Suitable to use on bleached	
Bases	Yes
General instructions	Once opened, ensure that the container lids are re-closed tightly. After repeated openings, check suitability of material for the intended purpose.

Disposal

In case of disposal use only the waste codes specified by your waste disposal authority.

Units of sale

25.00 L in 30 L cans
5.00 L in 6 L cans
200.00 L in 216 L drums

Safety

Observe instructions on the safety data sheet MSDS (Material Safety Data Sheet) and the label.

Other information

For commercial and industrial use only.

Date of last update **26.04.2016**

The suitability of the material shall be inspected by the manufacturer with respect to his/her requirements regarding quality, color, and the like, e.g. by a sample staining and/or sample varnishing. The above information is based on our testing and experience. Furthermore, the information does not represent any warranty of any characteristics and thus does also not represent the contractually agreed nature of the product. Additionally, the information does not claim any completeness and it is given without any warranties.