

The T3 GYS AUTO is a Synergic three phase MIG-MAG welding machine with 3 torch connectors. Ideal for car body repairs, it is recommended for welding steel, stainless steel, aluminium and for MIG Brazing of high-tensile strength steels (with CuSi3 and CuAl8 wires).

Synergic Mode



- The machine determines the optimum wire speed by selecting :
 - the type of wire
 - the wire diameter
 - the welding current

Spool gun (optional)

Upgradeable - the T3 GYS AUTO can be fitted with a Spool Gun torch. This motorised torch is suitable for 1kg/ø100mm wire reels of aluminium, stainless steel, copper and steel in ø0.8mm.

- Ideal for soft wire such as the AlSi5 or AlSi12 (recommended for car body repairs)
- Ease of use : adjust the wire speed directly on the Spool Gun torch.

4 Drive rolls motor



- Suitable for 5kg/ø200mm and 15kg/ø300mm wire reels.

Saving welding parameters


Memory save feature for each torch and activation of the 'last used' welding parameters (wire diameter, wire type & mode).



Accessories

Delivered with:
1 Steel torch 150A - 3m
1 Alu torch 150A - 3m
1 Earth clamp 200A - 3m
(regulator not included)

+ ADVANTAGES
















2 torches, 2 integrated wire feeders + 1 Spool Gun - The T3 GYS AUTO is a multifunction and flexible machine designed to weld 3 different types of wire at the same time. It saves time since it does not require to disassemble the torch and change the wire reel for another job.

Capable of welding:

- Soft wires: as AlSi and CuAl necessary for welding HLE/THLE metal sheets
- Aluminium wires
- Steel wires

CE - EN 60974-1

|  50/60hz |  |  min▷max |  ø mm |  100 200 300 |  |  équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica |  EN60974-1 (40°C) |  I _A (60%) |  X% (I ₂ max) |  cm/kg | Protected & compatible POWER GENERATOR (+/- 15%) | Spool Gun |
|---|---|--|---|--|--|---|--|--|---|--|---|--|
| 400V | 10A | 15▷200A | 0.6-1.0 |  ✓✓ |  | 0.6-0.8 | 2x0.8 | 110A | 150A 25% | 60x90x90 72 | 5 kVA | Option |
| 230/400V | 16/10A | | | | | 0.8-1.0 | | | | | | |