

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name: **PURIDUR-KARAT UV-FILTER**
FARBLOS, ANTIKMATT

Article number: 33550-7-0000

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture *Lacquer*

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

VOTTELER

Lackfabrik GmbH & Co. KG

Schwieberdinger Str. 97/102

70825 Korntal-Münchingen

Tel: 0711/9804-5

Fax: 0711/9804-722

Further information obtainable from:

Labor Sekretariat:

+49 (0)711 9804 - 721 (nur während den üblichen Bürozeiten)

msds@votteler.com

1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number)

GBK/Infotrac ID 90374 : (USA domestic) 1 800 535 5053 or international (001) 352 323 3500

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms GHS02, GHS07

Signal word *Danger*

Hazard-determining components of labelling:

n-butyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Version number 46

Revision: 19.01.2016

**Trade name: PURIDUR-KARAT UV-FILTER
FARBLOS, ANTIKMATT**

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains Reaction mass of .alpha.-3-(3-(2H- benzotriazol-2-yl)-5-tert-butyl-4- hydroxyphenyl)propionyl-.omega.-hydroxypoly(oxyethylene) and .alpha.- 3-(3-(2H-benzotriazol-2-yl)-5- tert-butyl-4-hydroxyphenyl)propionyl-.omega.-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene). CAS: 104810-47-1, 104810-48-2, 25322-68-3; EG-Nr.: 400-830-7, Additiv; R-43. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4 EINECS: 204-658-1	<i>n</i> -butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	25-50%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 67-64-1 EINECS: 200-662-2	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5-10%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-5%
	WGK 1, nicht kennzeichnungspflichtig, nicht flüchtig Aquatic Chronic 3, H412	2.5-5%
CAS: 54839-24-6 EINECS: 259-370-9	2-ethoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	0.5-2.5%
CAS: 112-07-2 EINECS: 203-933-3	2-butoxyethyl acetate Acute Tox. 4, H312; Acute Tox. 4, H332	0.5-2.5%
	Reaction mass of .alpha.-3-(3-(2H- benzotriazol-2-yl)-5-tert-butyl-4- hydroxyphenyl)propionyl-.omega.-hydroxypoly(oxyethylene) and .alpha.- 3-(3-(2H-benzotriazol-2-yl)-5- tert-butyl-4-hydroxyphenyl)propionyl-.omega.-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene). CAS: 104810-47-1, 104810-48-2, 25322-68-3; EG-Nr.: 400-830-7 Aquatic Chronic 2, H411; Skin Sens. 1, H317	< 0.5%
	Additiv; R-43 Skin Sens. 1, H317	< 0.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Version number 46

Revision: 19.01.2016

Trade name: PURIDUR-KARAT UV-FILTER
FARBLOS, ANTIKMATT

(Contd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Version number 46

Revision: 19.01.2016

Trade name: PURIDUR-KARAT UV-FILTER
FARBLOS, ANTIKMATT

(Contd. of page 3)

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm
Long-term value: 200 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm
Long-term value: 133 mg/m³, 20 ppm
Sk

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

· **As protection from splashes gloves made of the following materials are suitable:** Neoprene gloves

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Version number 46

Revision: 19.01.2016

Trade name: PURIDUR-KARAT UV-FILTER
FARBLOS, ANTIKMATT

(Contd. of page 4)

· **Not suitable are gloves made of the following materials:**

Leather gloves
Strong material gloves

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Specific type
Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C

· **Flash point:** -17 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:	2.1 Vol %
Upper:	13.0 Vol %

· **Vapour pressure at 20 °C:** 233 hPa

Density at 20 °C:	0.945 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic at 20 °C:	115 mPas
Kinematic:	Not determined.

· **Solvent content:**

Organic solvents:	74.9 %
Water:	0.0 %

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Version number 46

Revision: 19.01.2016

Trade name: PURIDUR-KARAT UV-FILTER
FARBLOS, ANTIKMATT

(Contd. of page 5)

· **9.2 Other information** *No further relevant information available.*

* **SECTION 10: Stability and reactivity**

- **10.1 Reactivity** *No further relevant information available.*
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **10.3 Possibility of hazardous reactions** *No dangerous reactions known.*
- **10.4 Conditions to avoid** *No further relevant information available.*
- **10.5 Incompatible materials:** *No further relevant information available.*
- **10.6 Hazardous decomposition products:** *No dangerous decomposition products known.*

* **SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** *Based on available data, the classification criteria are not met.*
- **Primary irritant effect:**
- **Skin corrosion/irritation** *Based on available data, the classification criteria are not met.*
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** *Based on available data, the classification criteria are not met.*
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** *Based on available data, the classification criteria are not met.*
- **Carcinogenicity** *Based on available data, the classification criteria are not met.*
- **Reproductive toxicity** *Based on available data, the classification criteria are not met.*
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** *Based on available data, the classification criteria are not met.*
- **Aspiration hazard** *Based on available data, the classification criteria are not met.*

* **SECTION 12: Ecological information**

- **12.1 Toxicity**
- **Aquatic toxicity:** *No further relevant information available.*
- **12.2 Persistence and degradability** *No further relevant information available.*
- **12.3 Bioaccumulative potential** *No further relevant information available.*
- **12.4 Mobility in soil** *No further relevant information available.*
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **12.6 Other adverse effects** *No further relevant information available.*

* **SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Version number 46

Revision: 19.01.2016

Trade name: PURIDUR-KARAT UV-FILTER
FARBLOS, ANTIKMATT

(Contd. of page 6)

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263

- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT

· **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3

· **IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3

· **14.4 Packing group**

- **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:**

- **Marine pollutant:** No

· **14.6 Special precautions for user**

- **Warning:** Flammable liquids.
- **Danger code (Kemler):** 33
- **EMS Number:** F-E, S-E
- **Stowage Category** B

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **Transport category** 2

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Version number 46

Revision: 19.01.2016

Trade name: PURIDUR-KARAT UV-FILTER
FARBLOS, ANTIKMATT

(Contd. of page 7)

· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category** P5c **FLAMMABLE LIQUIDS**
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
 - **National regulations:**
 - **Technical instructions (air):**
- | Class | Share in % |
|-------|------------|
| 74.94 | % |
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- **Department issuing SDS:** Abteilung Entwicklung
- **Contact:** Jeweiliger Produktverantwortlicher
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 13.04.2016

Version number 46

Revision: 19.01.2016

Trade name: PURIDUR-KARAT UV-FILTER
FARBLOS, ANTIKMATT

(Contd. of page 8)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· *** Data compared to the previous version altered.**

GB