
/OTTELER

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 03.05.2016

Version number 5

Revision: 03.05.2016



(Contd. on page 2)

Printing date 03.05.2016

Version number 5

Revision: 03.05.2016

Trade name: HYDRO-LACK **GRAPHITSCHWARZ, SEIDENMATT**

(Contd. of page 1)

SECTION 3: Composition/information on ingredients		
• 3.2 Chemical characterisation: Mixtures • Description: Mixture of substances listed below with nonhazardous additions.		
· Dangerous compone	Dangerous components:	
CAS: 111-90-0 EINECS: 203-919-7	2-(2-ethoxyethoxy)ethanol Eye Irrit. 2, H319	5-10%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	5-10%
CAS: 112-34-5 EINECS: 203-961-6	2-(2-butoxyethoxy)ethanol Eye Irrit. 2, H319	5-10%
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	< 0.5%
· Additional informati	on: For the wording of the listed hazard phrases refer to section 16.	

tional information: For the wording of the listed hazard phi

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Not required.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

- · 6.4 Reference to other sections See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 3)

GR

Printing date 03.05.2016

Version number 5

Revision: 03.05.2016

Trade name: HYDRO-LACK

GRAPHITSCHWARZ, SEIDENMATT

(Contd. of page 2)

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly.

· Information about fire - and explosion protection: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

 $\cdot \textit{Further information about storage conditions: Keep container tightly sealed.}$

 \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol WEL Short-term value: 246 mg/m³, 50 ppm

Long-term value: 123 mg/m³, 25 ppm Sk, BMGV

112-34-5 2-(2-butoxyethoxy)ethanol

WEL Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm

1333-86-4 Carbon black

WEL Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine Medium: urine

Sampling time: post shift

Parameter: butoxyacetic acid

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

- **Respiratory protection:** Not required.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 4)

GB

Printing date 03.05.2016

Version number 5

Revision: 03.05.2016

Trade name: HYDRO-LACK

GRAPHITSCHWARZ, SEIDENMATT

(Contd. of page 3)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

- As protection from splashes gloves made of the following materials are suitable: Neoprene gloves • Not suitable are gloves made of the following materials:
- Leather gloves

Strong material gloves • Eye protection:



Tightly sealed goggles

9.1 Information on basic physical a General Information	und chemical properties	
Appearance:		
Form:	Fluid	
Colour:	Black	
Odour:	Specific type	
Odour threshold:	Not determined.	
pH-value at 20 °C:	7.5	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C	
Flash point:	>100 °C	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	190 °C	
Decomposition temperature:	Not determined.	
Self-igniting:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure at 20 °C:	23 hPa	
Density at 20 °C:	1.046 g/cm ³	
Relative density	Not determined.	
Vapour density	Not determined.	

- GB

Printing date 03.05.2016

Version number 5

Revision: 03.05.2016

Trade name: HYDRO-LACK GRAPHITSCHWARZ, SEIDENMATT

		(Contd. of page 4
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Fully miscible.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic at 20 °C:	38 s (DIN 53211/4)	
· Solvent content:		
Organic solvents:	21.0 %	
Water:	50.8 %	
• 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- \cdot Serious eye damage/irritation
- Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}$
- STOT-single exposure Based on available data, the classification criteria are not met.
- $\cdot \textbf{STOT-repeated exposure} Based on available data, the classification criteria are not met.$
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- \cdot 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)

GB

Printing date 03.05.2016

Version number 5

Revision: 03.05.2016

(Contd. of page 5)

Trade name: HYDRO-LACK

GRAPHITSCHWARZ, SEIDENMATT

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• European	waste catalogue
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF
	COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS

	COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS
	AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 16	aqueous sludges containing paint or varnish other than those mentioned in 08 01 15

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN-Number	¥7 · 1	
ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ann	ex II of	
Marpol and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

(Contd. on page 7)

Printing date 03.05.2016

Version number 5

Revision: 03.05.2016

Trade name: HYDRO-LACK

GRAPHITSCHWARZ, SEIDENMATT

(Contd. of page 6)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations:

· Technical instructions (air):



• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H400 Very toxic to aquatic life.

· Department issuing SDS: Abteilung Entwicklung

· Contact: Jeweiliger Produktverantwortlicher

· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

 \cdot * Data compared to the previous version altered.

GB